

2.5MW-5MWh-2h/2.5MW-10MWh-4h Centralized Liquid-Cooled Energy Storage System



Flexible Solutions

- Supports multiple battery system configuration options to meet long-duration charging and discharging needs
- Modular design enables convenient and efficient maintenance operations in later stages
- Supports side-by-side and back-to-back layouts, reducing project footprint by 40%

Long Lifespan

- Full system cycle life exceeding 8,000 cycles
- Multi-level energy balancing management, efficient intelligent air-cooling, and liquid-cooling systems ensure full lifecycle protection


High Reliability

- PACK-level IP67 and cabinet-level IP54 rating, resistant to harsh operating environments
- Adopts three-level fire control linkage strategy, with the whole unit reaching IP54 protection class
- Supports operation at a maximum altitude of 4000 meters

High Efficiency

- 314Ah large PACK design reduces levelized cost of electricity (LCOE) by over 16%
- Efficient liquid-cooling system enhances both battery lifespan and system discharge capacity
- Prefabricated containerized system delivery shortens construction time by 30%

Topology



Product Specifications	2.5MW/5MWh	2.5MW/10MWh
DC-side		
Cell type	3.2V/314Ah	
System Battery Configuration	416S1P×12	416S1P×12×2
Battery Rated Capacity	5015.96kWh	10031.92kWh
Battery Voltage Range	1164.8V~1497.6V	
The AC-side PCS parameters		
AC-Side Rated Power	2500kVA	
AC-Side Voltage Distortion Rate	<3%（rated power）	
DC Component	≤0.5%（rated power）	
AC-Side Rated Voltage	AC690V	
Grid Voltage Range	586.5V~759V	
Power Factor	>0.99（rated power）	
Reactive Power Adjustable Range	-105%~105%	
Rated Grid Frequency	50Hz	
Grid Frequency Range	45Hz~55Hz	
Isolation Method	Transformer Isolation	
Transformer Parameters		
Rated Power	2750kVA	
Voltage Ratio	35kV/0.69kV	
Transformer Connection Group	Dy11	
System Parameters		
PCS&Transformer Dimensions (W x H x D)	6800×3100×3000mm（Dry-type Transformer）	
Battery Container Dimensions (W x H x D)	6180×2896×2438mm	6180×2896×2438mm（×2）
PCS&Transformer Weight	17T	
Battery Container Weight	≤42T	≤42T（×2）
IP Level / Corrosion-proof Grade	IP54/C3（C5 Optional）	
Operating Temperature Range	-30℃~50℃	
Operating Humidity Range	0%~95%（Non-condensing）	
Max. Operating Altitude	4000m（Derated Above 3000m）	
Cooling Method	Liquid Cooling	
Converter Cooling Method	Intelligent Air Cooling	
Fire Protection System	Perfluorohexanone / Water	
System Communication Interface	LAN	
External System Communication Protocol	IEC61850、IEC104、MODBUS-TCP	

East Energy Storage Technology Co., Ltd.

EAST Group : No.1, 5th Road, Songshan Lake Headquarters, Dongguan City, Guangdong Province

Xi'an R&D Center: No. 70 Jinye Road, High tech Zone, Xi'an City, Shaanxi Province

*If there are any changes to the product size and parameters, the latest information shall prevail without further notice.



Our WeChat QR code